



Speed controllers type Varionys M

Mono-phased speed variator

Brand

France Air

Application

- Electronic speed variator, mono-phased, shielded
- Protected to overcurrent by the mean of fusible
- Fixed output of 230V to control auxiliary (e.g. gas electrovalve)

Composition

- Plastic enclosure, ABS
- Dimensions: 164 x 104 x 77 mm
- Varionys M1: 0.400 kg
- Varionys M3: 0.520 kg
- Varionys M6: 0.580 kg
- Varionys M6: 0.650 kg
- Supply: 230 Vac, +/-15%, - 50 +/-2 Hz
- Protection to overcurrent
- IP54
- Storage temperature: -10 - 35°C
- Usage temperature: -10 - 45°C
- Directive CEM: 2004 / 108/ CEE
- Directive BT : 2006/ 95/ CEE

Order example

Varionys M 1

Varionys M= type

1 : max current

Models		
Model	Max Current (A)	Fusible
Varionys M1	1	5 x 20 mm 1.25A Type T-991 505
Varionys M3	3	5 x 20 mm 3.15A Type T-991 506
Varionys M6	6	5 x 20 mm 6.30A Type T-991 507
Varionys M8	8	5 x 20 mm 8.00A Type T-991 508



Wiring diagram



Declaration

