



Duct connections for insulated PPS plenum box & plate type PPS-APD

Duct connector in ABS for mounting into (insulated) panels with thickness up to 25 mm

Brand

- Cairox

Application

- To create a duct connection on the insulated polystyrene plenum box **PPS-P**
- To create a duct connection in **PIR** plates
- To create a duct connection on regular galvanized steel plenum boxes
- Available in duct size Ø125, Ø160, Ø200 and Ø250

Material

- ABS

Composition

- Threaded inner part for placement from the inside through the panel
- Threaded outer part with duct connection to be screwed over innerpart
- Flexible duct clamps for easy and secure mounting of flexible ducts

Accessories

- Regulating valve **PPS-CRC**, to be mounted in the duct connector

Order example

- **PPS-APD 200 + PPS-CRC 200**

Explication


PPS-APD = ABS duct connector

200 = Connection diameter

Accessories

PPS-CRC = Volume damper

200 = Size of connection



Dimensions						
	ØA [mm]	ØB [mm]	ØC [mm]	ØD [mm]	L [mm]	L1 [mm]
PPS-APD 125	123	112	155	118	51	40
PPS-APD 160	155	143	185	150	51	40
PPS-APD 200	195	183	225	190	51	40
PPS-APD 250	245	233	275	240	51	40