

- Multi-leaf dampers, fins 100 mm
- Standard, 165 mm blades



Multi-leaf dampers type JS 251

Multi-leaf dampers in galvanized steel.

Application

- For airstream regulation in ventilation and airconditioning systems

Material

- Galvanized steel blades, frame, and round axle
- Aluminium gears
- Polyamid bearings

Colour

- Galvanized steel

Composition

- Galvanized steel aerodynamic designed regulation blades of 165 mm width containing aluminium gears for simultanious counter-rotating operation of the damper
- Galvanized steel axle of Ø 12 mm and length 100 mm mounted on one of the above blades, which extends 67 mm outside the damperflanges. Axe with borehole at its end to easily mount axle extension LOA 100 M or LOA 150 M (upon request), when a longer axle is required.
- Galvanized steel housing with depth of 175mm and flange of 30mm, made out of 2 vertical panels with polyamid bearings and 2 horizontal panels, all welded together
- All dampers are made to measure. To obtain the exact height of the damper when in-between sizes are ordered, the upper and lower frame will be bended towards or away from the middle of the damper (see drawing), to make a excellent fit with as much as possible standard fitted blades. Due to this fact the free area of the damper can become less than the opening of the LXH dimension.

Mounting

- To be mounted between rectangular ducts with flanges of 30 mm
- To be surface mounted on wall, floor or ceiling

Accessories

- Manual control handle with fixing system type **MCS-251/255**
- Horizontal sealing between the valves available upon request **(+10%)**
- Mounted axle extensions type **LOA 100 M, LOA 150 M**
- Extra axle available upon request
- Square axle end of 9 X 9 mm type **SQE**
- Actuators **BELIMO**
- Alternative bearings:
 - PTFE bearings for low and high temperature applications type **TBS** (from -50°C to 200°C) and pressures till 2000Pa
 - Brass bearings for high temperature applications type **MBS** (up to 250°C)
 - Ball bearings for high pressure applications type **BBS** (up to 80°C and 2500Pa)
- Horizontal mounted coupling system type **HVM**
- Alternative outer-mechanism (for high temperature applications)
 - Counter-rotating blades **(+20%)**
 - Parallel moving blades **(+20%)**
- Reinforced frames **(+5%)**
- Multi-leaf damper with vertical blades **(+15%)**
- Alternative construction materials
 - Aluminium **(x3.5)**
 - Stainless steel (INOX304) **(x5.6)**
 - Stainless steel (INOX316) **(x6.75)**
 - Aluminium blades with galvanized steel frame **(x1.75)**
- Version ATEX available upon request

Text for tender

- The multi-leaf volume control dampers shall be of the type in galvanized steel with counter-rotating blades, aluminium gears, round axle and polyamid bearings.
- ATC Type **JS 251**

Order example

- **JS 251, 1600, 1500, C30 + MCS-251/255**

Explanation

JS 251 = Type of multi-leaf damper**1600** = Length**1500** = Height**C30** = connection flange

Accessories (Optional)

MCS-251/255 = Manual control with fixing system

Torque

