



## Electrical heating batteries type CVA - MPX

Round electrical heating battery for connection of an external regulating signal 0-10V, maximum blowing temperature: 50°C. A minimum air speed of 1,5m/s is necessary for the battery. Available in diameters from 100 to 400 mm and capacities from 300 to 12000 W. Tension 230 or 400 VAC.

| Ø [mm]             | Min. Qv [m3/h] | Technical data |                         |                         |
|--------------------|----------------|----------------|-------------------------|-------------------------|
|                    |                | V/50Hz         | P [kW]                  | In [A]                  |
| <b>CVA-MPX 100</b> | 40             | 1~230          | 0,3/0,6/0,9/1,2         | 1,4/2,8/4,1/5,5         |
| <b>CVA-MPX 125</b> | 70             | 1~230          | 0,3/0,6/0,9/1,2/1,5/1,8 | 1,4/2,8/4,1/5,5/6,8/8,2 |
| <b>CVA-MPX 160</b> | 110            | 1~230          | 1,2/2,0/2,4             | 5,5/9,1/10,9            |
|                    |                | 2~400          | 3,0/5,0/6,0             | 7,9/13,2/15,8           |
|                    |                | 3~400          | 6                       | 8,70                    |
| <b>CVA-MPX 200</b> | 170            | 1~230          | 1,2/2,0/2,4             | 5,5/9,1/10,9            |
|                    |                | 2~400          | 3,0/5,0/6,0             | 7,9/13,2/15,8           |
|                    |                | 3~400          | 6                       | 8,70                    |
| <b>CVA-MPX 250</b> | 270            | 1~230          | 1,2/2,0/2,4             | 5,5/9,1/10,9            |
|                    |                | 2~400          | 3,0/5,0/6,0             | 7,9/13,2/15,8           |
|                    |                | 3~400          | 6,0/9,0                 | 8,7/13,0                |
| <b>CVA-MPX 315</b> | 415            | 1~230          | 1,2/2,0/2,4             | 5,5/9,1/10,9            |
|                    |                | 2~400          | 3,0/5,0/6,0             | 7,9/13,2/15,8           |
|                    |                | 3~400          | 6,0/9,0/12,0            | 8,7/13,0/17,3           |
| <b>CVA-MPX 400</b> | 690            | 2~400          | 3,0/5,0/6,0             | 7,9/13,2/15,8           |
|                    |                | 3~400          | 6,0/9,0/12,0            | 8,7/13,0/17,3           |